TP-Link TD-W8901N

- Establish a connection between the device and the router via network cable or Wi-Fi
- Open your web browser and type the default IP Address 192.168.1.1 in the address bar



- You should now see the router login page with 2 text fields where you can type a username and a password
- The default username is admin and password is admin

	¥.	
The server 19	2.168.1.1 at TD-W8901G requires a userna	ame and password.
Warning: This ent in an insi connection).	server is requesting that your username a cure manner (basic authentication witho	and password be ut a secure
	admin	
	•••••	
	Remember my credentials	
	0	Cancel

- After typing username and password , click "Login" and now you should see modem's control panel
- Click interface setup then wireless
- In the SSID textbox type Wi-Fi Name , and make sure Authentication type is WPA2-PSK
- In Pre-Shared key textbox enter Wi-Fi password (safest passwords are long and contain at least 8 digits of mixed letters, and numbers)
- Once done click Save

Interface	Quick Start	Interface Setup	Advanced Setup	Access Management	Maintenance	Status	Helj
	Internet	LAN	Wireless	;			
Access Point Settings		Access Point :	Activated O	Deactivated			
	D	Channel :	: LEBANON ✓ 09 ✓ Current Channel: 9				
	Bea	CON Interval(ms) : CTS Threshold :	2347 (range: 1500~2347)				
		Fragmentation .	2346 (range: 256~2346, even numbers only)				
		DTIM(ms) :	: 1 (range: 1~255)				
		Wireless Mode :	802.11b+g+n 🗸]			
11n Settings							
	Ch	annel Bandwidth :	20/40 MHz 🗸				
	Ex	tension Channel :	below the control	channel 💙			
		Guard Interval :	AUTO V				
		WMM :	. [AUTU ♥]	icable			
Multiple SSIDs Settings				Sable			
		SSID Index :	1 🗸				
		Broadcast SSID :	• Yes O No				
		Use QSS :	● Yes ○ No				۸
QSS Settings							
		QSS state :	Configured				
		QSS mode :	O PIN code	PBC			
		QSS progress :	Idle				
		SSID :	TP-LINK				
	Aut	hentication Type :	WPA2-PSK	✓			
WPA-PSK							
		Encryption :	TKIP 🗸			_	
		Pre-Shared Key :	12345678			$\leq \Box$	
WDS Settings							
		WDS Mode :	🔿 On 💿 Off				
	WDS	Encryption Type :					
		WDS Key : Mac Address #1 :	00:00:00:00:00:00:0	0			
		Mac Address #2 :	00:00:00:00:00:00:0	0			
		Mac Address #3 :	00:00:00:00:00:0	0			
	l	Mac Address #4 :	00:00:00:00:00:0	0			
Vireless MAC Address Filter							
		Active :	Activated O	Deactivated			
		Action : Mac Address #1 :	Deny Association	the follow Wireles	s LAN station(s) associ	ation.	
		Mac Address #1	00:00:00:00:00:00:0	0			
		Mac Address #3	00:00:00:00:00:0	0			
		Mac Address #4 :	00:00:00:00:00:0	0			
		Mac Address #5 :	00:00:00:00:00:00	0			
		Mac Address #6 :		0			
		Mac Address #8 :	00:00:00:00:00:00:0	0			
							A
			SAVE CANC	EL			6